





N- and P-Channel 12-V (D-S) MOSFET

PRODUCT SUMMARY				
	V _{DS} (V)	R _{D(on)} (Ω)	I _D (A)	Q _g (Typ.)
N-Channel	12	0.040 at V _{GS} = 4.5 V	4.5 ^a	4.5 nC
		0.048 at V _{GS} = 2.5 V	4.5 ^a	
		0.063 at V _{GS} = 1.8 V	4.5 ^a	
P-Channel	- 12	0.070 at V _{GS} = - 4.5 V	- 4.5 ^a	5 nC
		0.100 at V _{GS} = - 2.5 V	- 4.5 ^a	
		0.140 at V _{GS} = - 1.8 V	- 4.5 ^a	

PowerPAK SC-70-6 Dual



Marking Code
Part # code: EAX
• XXX
Lot Traceability and Date code



N-Channel MOSFET

P-Channel MOSFET

Ordering Information: SiA511DJ-T1-GE3 (Lead (Pb)-free and Halogen-free)

FEATURES

- Halogen-free
- TrenchFET® Power MOSFETs
- New Thermally Enhanced PowerPAK® SC-70 Package
 - Small Footprint Area
 - Low On-Resistance

RoHS
COMPLIANT

APPLICATIONS

- Load Switch for Portable Devices

ABSOLUTE MAXIMUM RATINGS T _A = 25 °C, unless otherwise noted				
Parameter	Symbol	N-Channel	P-Channel	Unit
Drain-Source Voltage	V _{DS}	12	- 12	
Gate-Source Voltage	V _{GS}	± 8		V
Continuous Drain Current (T _J = 150 °C)	T _C = 25 °C	I _D	4.5 ^a	A
	T _C = 70 °C		4.5 ^a	
	T _A = 25 °C		4.5 ^{a, b, c}	
	T _A = 70 °C		4.5 ^{a, b, c}	
Pulsed Drain Current	I _{DM}	20	- 10	
Source Drain Current Diode Current	T _C = 25 °C	I _S	4.5 ^a	
	T _A = 25 °C		1.6 ^{b, c}	
Maximum Power Dissipation	T _C = 25 °C	P _D	6.5	W
	T _C = 70 °C		5	
	T _A = 25 °C		1.9 ^{b, c}	
	T _A = 70 °C		1.2 ^{b, c}	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	- 55 to 150		°C
Soldering Recommendations (Peak Temperature) ^{d, e}		260		

THERMAL RESISTANCE RATINGS						
Parameter	Symbol	N-Channel		P-Channel		Unit
		Typ.	Max.	Typ.	Max.	
Maximum Junction-to-Ambient ^{b, f}	t ≤ 5 s	R _{thJA}	52	65	52	65
Maximum Junction-to-Case (Drain)	Steady State	R _{thJC}	12.5	16	12.5	16

Notes:

- a. Package limited.
- b. Surface Mounted on 1" x 1" FR4 board.
- c. t = 5 s.
- d. See Solder Profile (<http://www.vishay.com/ppg?73257>). The PowerPAK SC-70 is a leadless package. The end of the lead terminal is exposed copper (not plated) as a result of the singulation process in manufacturing. A solder fillet at the exposed copper tip cannot be guaranteed and is not required to ensure adequate bottom side solder interconnection.
- e. Rework Conditions: manual soldering with a soldering iron is not recommended for leadless components.
- f. Maximum under Steady State conditions is 110 °C/W.

SPECIFICATIONS $T_J = 25^\circ\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit		
Static								
Drain-Source Breakdown Voltage	V_{DS}	$V_{GS} = 0 \text{ V}, I_D = 250 \mu\text{A}$	N-Ch	12		V		
		$V_{GS} = 0 \text{ V}, I_D = -250 \mu\text{A}$	P-Ch	- 12				
V_{DS} Temperature Coefficient	$\Delta V_{DS}/T_J$	$I_D = 250 \mu\text{A}$	N-Ch		12	mV/ $^\circ\text{C}$		
		$I_D = -250 \mu\text{A}$	P-Ch		- 7			
$V_{GS(\text{th})}$ Temperature Coefficient	$\Delta V_{GS(\text{th})}/T_J$	$I_D = 250 \mu\text{A}$	N-Ch		- 2.8			
		$I_D = -250 \mu\text{A}$	P-Ch		2.1			
Gate Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = 250 \mu\text{A}$	N-Ch	0.4	1	V		
		$V_{DS} = V_{GS}, I_D = -250 \mu\text{A}$	P-Ch	- 0.4	- 1			
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0 \text{ V}, V_{GS} = \pm 8 \text{ V}$	N-Ch		± 100	nA		
			P-Ch		± 100			
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 12 \text{ V}, V_{GS} = 0 \text{ V}$	N-Ch		1	μA		
		$V_{DS} = -12 \text{ V}, V_{GS} = 0 \text{ V}$	P-Ch		- 1			
		$V_{DS} = 12 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 55^\circ\text{C}$	N-Ch		10			
		$V_{DS} = -12 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 55^\circ\text{C}$	P-Ch		- 10			
On-State Drain Current ^b	$I_{D(\text{on})}$	$V_{DS} \geq 5 \text{ V}, V_{GS} = 4.5 \text{ V}$	N-Ch	15		A		
		$V_{DS} \leq -5 \text{ V}, V_{GS} = -4.5 \text{ V}$	P-Ch	- 8				
Drain-Source On-State Resistance ^b	$R_{DS(\text{on})}$	$V_{GS} = 4.5 \text{ V}, I_D = 4.2 \text{ A}$	N-Ch		0.033	0.040	Ω	
		$V_{GS} = -4.5 \text{ V}, I_D = -3.3 \text{ A}$	P-Ch		0.058	0.070		
		$V_{GS} = 2.5 \text{ V}, I_D = 3.8 \text{ A}$	N-Ch		0.039	0.048		
		$V_{GS} = -2.5 \text{ V}, I_D = -2.8 \text{ A}$	P-Ch		0.082	0.100		
		$V_{GS} = 1.8 \text{ V}, I_D = 1.6 \text{ A}$	N-Ch		0.051	0.063		
		$V_{GS} = -1.8 \text{ V}, I_D = -0.7 \text{ A}$	P-Ch		0.111	0.140		
Forward Transconductance ^b	g_{fs}	$V_{DS} = 10 \text{ V}, I_D = 4.2 \text{ A}$	N-Ch		13		S	
		$V_{DS} = -10 \text{ V}, I_D = -3.3 \text{ A}$	P-Ch		9			
Dynamic^a								
Input Capacitance	C_{iss}	N-Channel $V_{DS} = 6 \text{ V}, V_{GS} = 0 \text{ V}, f = 1 \text{ MHz}$	N-Ch		400		pF	
			P-Ch		400			
Output Capacitance	C_{oss}		N-Ch		120			
			P-Ch		140			
Reverse Transfer Capacitance	C_{rss}		N-Ch		70			
			P-Ch		100			
Total Gate Charge	Q_g	$V_{DS} = 6 \text{ V}, V_{GS} = 8 \text{ V}, I_D = 5.5 \text{ A}$	N-Ch		7.5	12	nC	
		$V_{DS} = -6 \text{ V}, V_{GS} = -8 \text{ V}, I_D = -4.3 \text{ A}$	P-Ch		8	12		
Gate-Source Charge	Q_{gs}	N-Channel $V_{DS} = 6 \text{ V}, V_{GS} = 4.5 \text{ V}, I_D = 5.5 \text{ A}$	N-Ch		4.5	6.8		
			P-Ch		5	7.5		
			N-Ch		0.6			
			P-Ch		0.8			
Gate-Drain Charge	Q_{gd}	P-Channel $V_{DS} = -6 \text{ V}, V_{GS} = -4.5 \text{ V}, I_D = -4.3 \text{ A}$	N-Ch		0.8			
			P-Ch		1.4			
Gate Resistance	R_g	$f = 1 \text{ MHz}$	N-Ch		2.5		Ω	
			P-Ch		7			

Notes:

a. Guaranteed by design, not subject to production testing.

b. Pulse test; pulse width $\leq 300 \mu\text{s}$, duty cycle $\leq 2\%$.



New Product

SiA511DJ

Vishay Siliconix

SPECIFICATIONS $T_J = 25^\circ\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit	
Dynamic^a							
Turn-On Delay Time	$t_{d(on)}$	N-Channel $V_{DD} = 6 \text{ V}, R_L = 1.4 \Omega$ $I_D \geq 4.4 \text{ A}, V_{GEN} = 4.5 \text{ V}, R_g = 1 \Omega$	N-Ch	5	10		
Rise Time	t_r		P-Ch	15	25		
Turn-Off Delay Time	$t_{d(off)}$	P-Channel $V_{DD} = -6 \text{ V}, R_L = 1.8 \Omega$ $I_D \geq -3.4 \text{ A}, V_{GEN} = -4.5 \text{ V}, R_g = 1 \Omega$	N-Ch	15	25		
Fall Time	t_f		P-Ch	25	40		
Turn-On Delay Time	$t_{d(on)}$	N-Channel $V_{DD} = 6 \text{ V}, R_L = 1.4 \Omega$ $I_D \geq 4.4 \text{ A}, V_{GEN} = 10 \text{ V}, R_g = 1 \Omega$	N-Ch	35	55		
Rise Time	t_r		P-Ch	20	30		
Turn-Off Delay Time	$t_{d(off)}$	P-Channel $V_{DD} = -6 \text{ V}, R_L = 1.8 \Omega$ $I_D \geq -3.4 \text{ A}, V_{GEN} = -10 \text{ V}, R_g = 1 \Omega$	N-Ch	15	25		
Fall Time	t_f		P-Ch	10	15		
Drain-Source Body Diode Characteristics							
Continuous Source-Drain Diode Current	I_S	$T_C = 25^\circ\text{C}$	N-Ch		4.5		
			P-Ch		-4.5		
Pulse Diode Forward Current ^a	I_{SM}		N-Ch		20		
			P-Ch		-10		
Body Diode Voltage	V_{SD}	$I_S = 4.4 \text{ A}, V_{GS} = 0 \text{ V}$	N-Ch	0.8	1.2		
		$I_S = -3.4 \text{ A}, V_{GS} = 0 \text{ V}$	P-Ch	-0.8	-1.2		
Body Diode Reverse Recovery Time	t_{rr}	N-Channel $I_F = 4.4 \text{ A}, di/dt = 100 \text{ A}/\mu\text{s}, T_J = 25^\circ\text{C}$	N-Ch	15	30		
Body Diode Reverse Recovery Charge	Q_{rr}		P-Ch	30	60		
Reverse Recovery Fall Time	t_a		N-Ch	8	20		
Reverse Recovery Rise Time	t_b		P-Ch	12	24		
			N-Ch	8.5			
			P-Ch	14			
			N-Ch	8.5			
			P-Ch	16			







Notes:






- a. Guaranteed by design, not subject to production testing.
- b. Pulse test; pulse width $\leq 300 \mu\text{s}$, duty cycle $\leq 2\%$.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

SiA511DJ



Vishay Siliconix

**N-CHANNEL TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted



N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

Source-Drain Diode Forward Voltage

On-Resistance vs. Gate-to-Source Voltage

Threshold Voltage

Single Pulse Power (Junction-to-Ambient)

Safe Operating Area, Junction-to-Ambient

SiA511DJ

Vishay Siliconix







**N-CHANNEL TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted






* The power dissipation P_D is based on $T_{J(\max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

Normalized Thermal Transient Impedance, Junction-to-Ambient

Normalized Thermal Transient Impedance, Junction-to-Foot



SiA511DJ

Vishay Siliconix



**P-CHANNEL TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted

P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

Soure-Drain Diode Forward Voltage

On-Resistance vs. Gate-to-Source Voltage

Threshold Voltage

Single Pulse Power, Junction-to-Ambient


* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified
Safe Operating Area, Junction-to-Ambient

P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

* The power dissipation P_D is based on T_{J(max)} = 150 °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted


Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?74592>.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.