

# IRF7701PbF

- Ultra Low On-Resistance
- P-Channel MOSFET
- Very Small SOIC Package
- Low Profile (< 1.1mm)
- Available in Tape & Reel
- Lead-Free

HEXFET® Power MOSFET


<b>V<sub>DSS</sub></b>	<b>R<sub>DS(on)</sub> max</b>	<b>I<sub>D</sub></b>
<b>-12V</b>	0.011@V <sub>GS</sub> = -4.5V	-10A
	0.015@V <sub>GS</sub> = -2.5V	-8.5A
	0.022@V <sub>GS</sub> = -1.8V	-7.0A

## Description

HEXFET® power MOSFETs from International Rectifier utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. This benefit, combined with the ruggedized device design, that International Rectifier is well known for, provides the designer with an extremely efficient and reliable device for use in battery and load management.

The TSSOP-8 package, has 45% less footprint area of the standard SO-8. This makes the TSSOP-8 an ideal device for applications where printed circuit board space is at a premium.

The low profile (<1.1mm) of the TSSOP-8 will allow it to fit easily into extremely thin application environments such as portable electronics and PCMCIA cards.



## Absolute Maximum Ratings

	Parameter	Max.	Units
V <sub>DS</sub>	Drain- Source Voltage	-12	V
I <sub>D</sub> @ T <sub>A</sub> = 25°C	Continuous Drain Current, V <sub>GS</sub> @ -4.5V	±10	A
I <sub>D</sub> @ T <sub>A</sub> = 70°C	Continuous Drain Current, V <sub>GS</sub> @ -4.5V	±8.0	
I <sub>DM</sub>	Pulsed Drain Current ①	±80	
P <sub>D</sub> @ T <sub>A</sub> = 25°C	Power Dissipation	1.5	W
P <sub>D</sub> @ T <sub>A</sub> = 70°C	Power Dissipation	0.96	
	Linear Derating Factor	12	mW/°C
V <sub>GS</sub>	Gate-to-Source Voltage	± 8.0	V
T <sub>J</sub> , T <sub>STG</sub>	Junction and Storage Temperature Range	-55 to + 150	°C

## Thermal Resistance

	Parameter	Max.	Units
R <sub>θJA</sub>	Maximum Junction-to-Ambient③	83	°C/W


# IRF7701PbF

International  
Rectifier

## Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(\text{BR})\text{DSS}}$	Drain-to-Source Breakdown Voltage	-12	—	—	V	$V_{\text{GS}} = 0\text{V}$ , $I_D = -250\mu\text{A}$
$\Delta V_{(\text{BR})\text{DSS}/\Delta T_J}$	Breakdown Voltage Temp. Coefficient	—	-0.006	—	$\text{V}^\circ\text{C}$	Reference to $25^\circ\text{C}$ , $I_D = -1\text{mA}$
$R_{\text{DS}(\text{on})}$	Static Drain-to-Source On-Resistance	—	—	0.011	$\Omega$	$V_{\text{GS}} = -4.5\text{V}$ , $I_D = -10\text{A}$ ②
		—	—	0.015		$V_{\text{GS}} = -2.5\text{V}$ , $I_D = -8.5\text{A}$ ②
		—	—	0.022		$V_{\text{GS}} = -1.8\text{V}$ , $I_D = -7.0\text{A}$ ②
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	-0.45	—	-1.2	V	$V_{\text{DS}} = V_{\text{GS}}$ , $I_D = -250\mu\text{A}$
$g_{\text{fs}}$	Forward Transconductance	21	—	—	S	$V_{\text{DS}} = -10\text{V}$ , $I_D = -10\text{A}$
$I_{\text{DSS}}$	Drain-to-Source Leakage Current	—	—	1.0	$\mu\text{A}$	$V_{\text{DS}} = -12\text{V}$ , $V_{\text{GS}} = 0\text{V}$
		—	—	-25		$V_{\text{DS}} = -9.6\text{V}$ , $V_{\text{GS}} = 0\text{V}$ , $T_J = 70^\circ\text{C}$
$I_{\text{GSS}}$	Gate-to-Source Forward Leakage	—	—	-100	$\text{nA}$	$V_{\text{GS}} = -8.0\text{V}$
	Gate-to-Source Reverse Leakage	—	—	100		$V_{\text{GS}} = 8.0\text{V}$
$Q_g$	Total Gate Charge	—	69	100	$\text{nC}$	$I_D = -8.0\text{A}$
$Q_{\text{gs}}$	Gate-to-Source Charge	—	9.1	14		$V_{\text{DS}} = -9.6\text{V}$
$Q_{\text{gd}}$	Gate-to-Drain ("Miller") Charge	—	21	32		$V_{\text{GS}} = -4.5\text{V}$ ②
$t_{\text{d}(\text{on})}$	Turn-On Delay Time	—	19	—	$\text{ns}$	$V_{\text{DD}} = -6.0\text{V}$
$t_r$	Rise Time	—	20	—		$I_D = -1.0\text{A}$
$t_{\text{d}(\text{off})}$	Turn-Off Delay Time	—	240	—		$R_D = 6.0\Omega$
$t_f$	Fall Time	—	220	—		$V_{\text{GS}} = -4.5\text{V}$ ②
$C_{\text{iss}}$	Input Capacitance	—	5050	—	$\text{pF}$	$V_{\text{GS}} = 0\text{V}$
$C_{\text{oss}}$	Output Capacitance	—	1520	—		$V_{\text{DS}} = -10\text{V}$
$C_{\text{rss}}$	Reverse Transfer Capacitance	—	1120	—		$f = 1.0\text{MHz}$

## Source-Drain Ratings and Characteristics


	Parameter	Min.	Typ.	Max.	Units	Conditions
$I_S$	Continuous Source Current (Body Diode)	—	—	-1.5	A	MOSFET symbol showing the integral reverse p-n junction diode.
$I_{\text{SM}}$	Pulsed Source Current (Body Diode) ①	—	—	-80		
$V_{\text{SD}}$	Diode Forward Voltage	—	—	-1.2	V	$T_J = 25^\circ\text{C}$ , $I_S = -1.5\text{A}$ , $V_{\text{GS}} = 0\text{V}$ ②
$t_{\text{rr}}$	Reverse Recovery Time	—	52	78	ns	$T_J = 25^\circ\text{C}$ , $I_F = -1.5\text{A}$
$Q_{\text{rr}}$	Reverse Recovery Charge	—	53	80	nC	$dI/dt = 100\text{A}/\mu\text{s}$ ②

### Notes:


① Repetitive rating; pulse width limited by max. junction temperature.

② Pulse width  $\leq 300\mu\text{s}$ ; duty cycle  $\leq 2\%$ .


③ When mounted on 1 inch square copper board,  $t < 10 \text{ sec}$




**Fig 1.** Typical Output Characteristics



**Fig 2.** Typical Output Characteristics




**Fig 3.** Typical Transfer Characteristics




**Fig 4.** Normalized On-Resistance  
Vs. Temperature

# IRF7701PbF


International  
Rectifier




**Fig 5.** Typical Capacitance Vs.  
Drain-to-Source Voltage




**Fig 6.** Typical Gate Charge Vs.  
Gate-to-Source Voltage




**Fig 7.** Typical Source-Drain Diode  
Forward Voltage




**Fig 8.** Maximum Safe Operating Area




**Fig 9.** Maximum Drain Current Vs.  
Case Temperature



**Fig 10a.** Switching Time Test Circuit




**Fig 10b.** Switching Time Waveforms




**Fig 10.** Typical Effective Transient Thermal Impedance, Junction-to-Ambient

# IRF7701PbF


International  
Rectifier




**Fig 11.** Typical On-Resistance Vs. Gate Voltage




**Fig 12.** Typical On-Resistance Vs. Drain Current




**Fig 13a.** Basic Gate Charge Waveform



**Fig 13b.** Gate Charge Test Circuit




**Fig 14.** Threshold Voltage Vs. Temperature




**Fig 15.** Typical Power Vs. Time

**TSSOP8 Package Outline**

Dimensions are shown in millimeters (inches)



SYMBOL	MO-153AA DIMENSIONS					
	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	--	--	1.20	--	--	.0472
A1	0.05	--	0.15	.0020	--	.0059
A2	0.80	1.00	1.05	.032	.039	.041
b	0.19	--	0.30	.0075	--	.0118
c	0.09	--	0.20	.0036	--	.0078
D	2.90	3.00	3.10	.115	.118	.122
E	6.40 BSC			.251 BSC		
E1	4.30	4.40	4.50	.170	.173	.177
e	0.65 BSC			.0256		
L	0.45	0.60	0.75	.0178	.0236	.0290
L1	0.25 BSC			.010 BSC		
$\theta$	0°	8°	8°	0°	--	8°
aaa	0.10			.0039		
bbb	0.10			.0039		
ccc	0.05			.0019		
ddd	0.20			.0078		


LEAD ASSIGNMENTS

## NOTES


1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
2. DIMENSIONS ARE SHOWN IN MILLIMETERS AND INCHES.
3. CONTROLLING DIMENSION: MILLIMETER.
4. DATUM PLANE H IS LOCATED AS SHOWN.
5. DATUM A AND B TO BE DETERMINED AT DATUM PLANE H.
6. DIMENSIONS D AND E1 ARE MEASURED AT DATUM PLANE H.
7. DIMENSION L IS THE LEAD LENGTH FOR SOLDERING TO A SUBSTRATE.
8. OUTLINE CONFORMS TO JEDEC OUTLINE MO-153AA.

## TSSOP8 Part Marking Information

EXAMPLE: THIS IS AN IRF7702



## TSSOP-8 Tape and Reel Information



Data and specifications subject to change without notice.  
This product has been designed and qualified for the Consumer market.  
Qualification Standards can be found on IR's Web site.

**International**  
**IR** Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7903

Visit us at [www.irf.com](http://www.irf.com) for sales contact information. 12/2006