

RJ45 connector - CUC-IND-C1ZNI-S/R4QP8 - 1406334

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



RJ45 connector, Degree of protection: IP20, Number of positions: 8, 10 Gbps, Material: Zinc die-cast, Connection method: IDC, Connection cross section: AWG 23-22, Cable exit: straight, High degree of resistance to vibration; 360° shielding; one-piece design; special tool-free assembly

Why buy this product

- ☑ assembly without special tools
- ☑ One-Piece Design
- ☑ 360° shielding
- High shock and vibration resistance



Key Commercial Data

Packing unit	1 STK
GTIN	4 046356 760706
GTIN	4046356760706

Technical data

Mechanical characteristics

Number of positions	8
Connection profile	RJ45
Insertion/withdrawal cycles	≥ 750
Connection method	IDC
Connection cross section AWG	23 22 (solid)
	23 22 (stranded)
Max. cable diameter	5 mm 9 mm
External cable diameter	5 mm 9 mm
Cable exit	straight
Wire diameter including insulation	≤ 1.6 mm
Degree of protection	IP20
Design	RJ45, IP20



RJ45 connector - CUC-IND-C1ZNI-S/R4QP8 - 1406334

Technical data

Mechanical characteristics	
No. of cable outlets	1
Ambient conditions	
Ambient temperature (operation)	-40 °C 70 °C
Material data	
Flammability rating according to UL 94	V0
Housing material	Zinc die-cast
Electrical characteristics	
Number of positions	8
Transmission speed	10 Gbps
	10 Gbps
Frequency range	to 500 MHz
Standards and Regulations	
Flammability rating according to UL 94	V0
Environmental Product Compliance	
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Dimensional drawing



Approvals
Approvals
EAC

Ex Approvals



RJ45 connector - CUC-IND-C1ZNI-S/R4QP8 - 1406334

EAC

Approvals

Approval details

EAC

B.01742

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com